

XENON XP ACCESSORIES GUIDE



Honeywell

TABLE OF CONTENTS

- 3 WALL MOUNTS, STANDS, HOLDERS, AND COVERS
- 5 COMMUNICATION BASES, CHARGERS, AND BATTERIES
- 7 CABLES AND POWER SUPPLIES

WALL MOUNTS, STANDS, HOLDERS, AND COVERS



1950GSR-2-2-X
1950GHD-2-2-X
1950GSR-2USB-2-X
1950GHD-2USB-2-X

1950G Ratchet Stand

Provides a fixed stand for a corded scanner that enables presentation scanning and two-handed scanning. Scanner is built into the ratchet stand and not removeable.



50129064-001

Wall-Mount Cup

Holder Kit: Plastic bracket facilitates mounting of scanner to wall; two mounting screws included in kit.



STND-08R00-000-6

Rigid Presentation Stand – 3”

Stand: gray, 8 cm (3 in) height, rigid rod, large oval weighted base, cradle for Xenon™ 1900 and Xenon XP 1950 corded scanners.



STND-15R00-000-6

Rigid Presentation Stand – 6”

Stand: gray, 15 cm (6 in) height, rigid rod, large oval weighted base, Xenon cradle.



STND-22F00-001-6

Stand

Gray, 22 cm (9 in) height, flexible rod, large oval weighted base, Xenon cup.



STND-24F03-001-6

Stand

Black, 24cm (9.5”) height, flexible rod, medium oval weighted base, Xenon cup



VISOR-190X-XT

Extended Sun Visor

Extended sun visor for use in direct sunlight or extremely bright environments. For use with Xenon XP 1950 corded and 1952 cordless scanners.



VISOR 190X

Sun Visor

Sun visor for use in direct sunlight or extremely bright environments. For use with Xenon XP 1950 corded and 1952 cordless scanners.



UCOVERXENON

Retractable Lanyard Cover

Fabric cover for hanging the scanner from a retractable lanyard.



VMHOLDERE-21029

Forklift Holder

Forklift/vehicle-mounted holder for holding a Xenon XP 1950 corded scanner between scans.



300001501

Metal Bracket

Sheet metal bracket with pre-drilled holes enables horizontal or vertical mounting of a cordless system



HOLSTERE

Holder

Belt holster stores Xenon XP 1952, Xenon 1902, 3820, 3820i, 4820, or 4820i cordless scanner and one spare lithium-ion battery

WALL MOUNTS, STANDS, HOLDERS, AND COVERS

continued



HOLDER-001-D

Holder Kit

Plastic cup style holder facilitates mounting of Xenon corded scanner face first to desk or wall. Mounting screws included in kit



300001490

Plastic charge/communication base

Insert prevents the scanner from falling out of the base when the cordless system is subjected to turbulent movement..



AP-100BT-07N

Bluetooth Access Point

Access point for Xenon XP scanners. Class 2 Bluetooth, 10m (33'), up to 7 Xenon XP scanners can be connected, RS232/USB/KBW/IBM (cable sold separately)



200003829

Cordless Scanner End Cap

White, tool-free (thumbwheel) end cap for use with 1902h and Xenon XP 1952h with white disinfectant-ready housings

COMMUNICATION BASES, CHARGERS, AND BATTERIES



BAT-SCN01A

Battery Pack

Battery: Lithium-ion battery for Xenon 1902 and Xenon XP 1952 cordless scanners.



BAT-SCN05

Smart Battery Pack

Battery: Lithium-ion battery for Xenon XP 1952 cordless scanners.



SUPCAP-SCN05

SuperCap Pack

Chargeable super capacitor for Xenon XP 1952 and legacy Xenon 1902 Battery Free cordless scanners.



MB4-BAT-SCN01NAD06

4-Bay Battery Charger – Desk Mount

4-bay battery charger (NA) for use with Xenon 1902 and Xenon XP 1952 Lithium-ion batteries, NA desktop power supply (PS-050-4000D-NA), two mounting screws (100006897), and instructions (MBC-INST).



MB4-BAT-SCN01NAW06

4-Bay Battery Charger – Wall Mount

4-bay battery charger (NA) for use with Xenon 1902 and Xenon XP 1952 Lithium-ion batteries, NA wall-mount power supply (PS-050-4000W-NA), two mounting screws (100006897), and instructions (MBC-INST).



CCB10-010BT-07N

1952 Presentation CCB – Black (Battery)

Xenon XP 1952 Presentation CCB, black, 10 m (32.8 ft), Bluetooth®.



CCB11-010BT-07N

1952 Presentation CCB – Lyric White (Battery)

Xenon XP 1952 Presentation CCB, white, 10 m (32.8 ft), Bluetooth.



CCB12-010BT-HC

1952 Presentation CCB – Healthcare (Battery)

Xenon XP 1952 Presentation CCB, healthcare white, healthcare software, 10 m (32.8ft), Bluetooth.



CCB13-010BT-07N

1952 Desktop/Wall-Mount CCB – Black (Battery)

Xenon XP 1952 Horizontal CCB, black, 10 m (32.8 ft), Bluetooth.



CCB15-010BT-HC

1952 Desktop/Wall-Mount CCB – Healthcare (Battery)

Xenon XP 1952 Horizontal CCB, healthcare white, healthcare software, 10 m (32.8ft), Bluetooth.



CCB10-010BT-07N-BF

1952 Battery Free Presentation CCB

Xenon XP 1952 Presentation CCB, black, 10 m (32), Bluetooth



CCB11-010BT-07N-BF

1952 Battery Free Desktop/Wallmount CCB

Xenon XP 1952 Presentation CCB, black, 10 m (32), Bluetooth

COMMUNICATION BASES, CHARGERS, AND BATTERIES

continued



CCB12-010BT-HC-BF

1952 Battery Free Presentation CCB

Xenon XP 1952 Presentation CCB, white, 10 m (32), Bluetooth



CCB15-010BT-HC-BF

1952 Battery Free Desktop/Wallmount CCB

Xenon XP 1952 Presentation CCB, white, 10 m (32), Bluetooth











COB01

Charge-Only Base

Only 1 scanner can be charged at a time, power supply must be purchased separately.



CABLES AND POWER SUPPLIES

CONNECTION TYPE	PART NUMBER	DESCRIPTION	LENGTH	TYPE
Serial	CBL-020-300-C00	Cable: RS232 (5V signals), black, DB9 female, 3m (9.8'), coiled, 5V ext. power with option for host power on pin 9	3m	COILED
				
Serial	CBL-120-300-C00	Cable: RS232 (+/- 12V signals), black, DB9 female, 3m (9.8'), coiled, 5V ext. power with option for host power on pin 9	3m	COILED
				
Serial	CBL-220-300-C00	Cable: RS-232 (+5V signals), black, DB9 Male, 3 m (9.8 ft), coiled, external power with option for host power on pin 9 for connection to Wincor Beetle.	3m	COILED
				
Serial	CBL-420-300-C00	Cable: RS232 (5V signals), Honeywell Biopic Stratos Aux, black, 10 pin modular, 3m (9.8'), coiled, host power possible (dependent upon scanner and Stratos models)	3m	COILED
				
USB	CBL-500-150-S00	Cable: USB, Type A, HSM, 1.5m (5'), straight, 5V host power	1.5m	STRAIGHT
				
USB	CBL-500-300-S00	Cable: USB, black, Type A, 3m (9.8'), straight, 5V host power	3m	STRAIGHT
				
USB	CBL-500-500-C00	Cable: USB, black, Type A, 5m (16.4'), coiled, 5V host power	5m	COILED
				
USB	CBL-503-300-C00	Cable: USB, black, 12V locking, 3m (9.8'), coiled, 5V host power	3m	COILED
				


CABLES AND POWER SUPPLIES

continued

CONNECTION TYPE	PART NUMBER	DESCRIPTION	LENGTH	TYPE
Keyboard Wedge	CBL-720-300-C00	Cable: KBW, black, PS2, 3m (9.8'), coiled, 5V ext power with option of host power	3m	COILED



Serial	CBL-MAG-300-S00	Cable: RS-232 (5V signals), Magellan Aux Port, black, 10 pin modular, 3 m (9.8 ft), straight, external power with option for host scanner power.	3m	STRAIGHT
--------	-----------------	--	----	----------



46-00525-6

Power Supply – NA Plug

Power Supply: NA plug, 1.0A @ 5.2V
DC, 90–255V AC @ 50–60 Hz.



46-00526

Power Supply – EU Plug

Power Supply: EU plug, 1.0A @ 5.2V
DC, 90–255V AC @ 50–60 Hz.



46-00528

Power Supply – AU Plug

Power Supply: AU plug, 1.0A @ 5.2V
DC, 90–255V AC @ 50–60 Hz.



46-00529

Power Supply – CN Plug

Power Supply: CN plug, 1.0A @ 5.2V
DC, 90–255V AC @ 50–60 Hz.

For more information

sps.honeywell.com

Honeywell Safety and Productivity Solutions

855 S Mint St
Charlotte, NC 28202
800-582-4263
www.honeywell.com

Xenon XP Accessories Guide LTR | Rev B | 10/21
©2021 Honeywell International Inc.